

Emergency Contact Telephone Number

Please print or type in black ink (Do not use blue ink)

Form Approved OMB No. 0704-0188

UNIFORM HAZARDOUS WASTE MANIFEST		1. Generator's US EPA ID No. W.A.D.9.8.0.7.3.8.5.4.6	Manifest Document No. 9.7.0.0.9	2. Page 1 of 1	Information in the shaded areas is not required by Federal law.	
3. Generator's Name and Mailing Address ALASKAN COPPER WORKS 3200 Sixth Avenue South, Seattle, WA 98134				A. State Manifest Document Number		
4. Generator's Phone (206) 623-5801 X379				B. State Generator's ID		
5. Transporter 1 Company Name Allwaste Transportation & Remediation				C. State Transporter's ID		
6. US EPA ID Number A.D.063.547.996				D. Transporter's Phone 800-331-1030		
7. Transporter 2 Company Name				E. State Transporter's ID		
8. US EPA ID Number				F. Transporter's Phone		
9. Designated Facility Name and Site Address World Resources Company 8113 West Sherman Street Phoenix, Arizona 85043				G. State Facility's ID		
10. US EPA ID Number A.Z.D.9.8.0.7.3.5.5.0.0				H. Facility's Phone 602-233-9166		
11. US DOT Description (Including Proper Shipping Name, Hazard Class, and ID Number)				12. Containers	13. Total Quantity	14. Unit Wt/Vol
a. HM				No.	Type	
b. RQ, Hazardous waste, solid, n.o.s., (D007), 9, NA3077, III				02.8	D.M	2284.3 P
c.				.	.	.
d.				.	.	.
J. Additional Descriptions for Materials Listed Above				K. Handling Codes for Wastes Listed Above		
P.O. m 58820						
15. Special Handling Instructions and Additional Information 24 Hour Emergency Response: 1-800-424-9300 CHEMTREC (Use CHEMTREC company code "W0RR") Wear gloves & goggles						
16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national governmental regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford.						
Printed/Typed Name Gerald A. Thompson				Signature <i>Gerald A. Thompson</i>		Month Day Year 10/23/97
17. Transporter 1 Acknowledgement of Receipt of Materials				Signature <i>Corey Shepherd</i>		Month Day Year 10/23/97
Printed/Typed Name Corey Shepherd				Signature <i>Corey Shepherd</i>		Month Day Year 10/23/97
18. Transporter 2 Acknowledgement of Receipt of Materials				Signature		Month Day Year
Printed/Typed Name				Signature		Month Day Year
19. Discrepancy Indication Space						
20. Facility Owner or Operator: Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.						
Printed/Typed Name				Signature		Month Day Year

EPA Form 700-22 (Rev. 9-94) Pre-Title Edition 03/96

GENERATOR'S COPY

EPA Form 700-22 (Rev. 9-94)

AKC-0017820

NOTICE

TO: World Resource Company
8112 West Sherman Street
Phoenix, Arizona 85043

From: Alaskan Copper Works
628 South Hanford Street
Seattle, Washington 98134

SUBJECT: Land Disposal Restriction Notice

Manifest Number: 97009

Date of Shipment: 10-23-97

This shipment of material, which is being provided for recycling, is subject to the land disposal restrictions of 40 CFR, Part 268, Subpart D or the prohibitions specified in 268.32 or RCRA 3004(d). The applicable Land Disposal Restriction Information is provided in accordance with 40 CFR 268.7 and is shown below:

EPA Material Number	Regulated Constituent	Subcategory	Treatability Group	Treatment Standards	
				CFR Reference	Prohibition Level
D007	N/A	N/A	Nonwastewater	40 CFR 268.41 40 CFR 268.43	---

By: Gerald A. Thompson
Alaskan Copper Environmental Assistant

Material Safety Data Sheet

D007 Recyclable Material

Recycler's Facility Name and Site Address:

Issued: 3/18/94

World Resources Company

8113 West Sherman Street

Phoenix, Arizona 85043

Tel: 1-602-233-9166 Fax: 602-936-9164

Call CHEMTREC only in the event of emergencies during shipping that involve a spill, leak, fire, or accident (all calls are recorded)

For Emergencies During Shipping in the US or Canada, Day or Night, Call: **CHEMTREC 800-424-9300** (Use CHEMTREC Company Code "WRRR") For calls from other countries call: **202-483-7616 Collect**

Section 1

PRODUCT - MATERIAL IDENTIFICATION

Environmental Protection Agency (EPA) Waste Classification: D007

Generic Name: Chromium metal bearing sludge

Chemical Family: Non-Ferrous metal particulates

Synonym: Metallic Residues From High Frequency Burning Table

DOT Shipping Name: RQ, Hazardous Waste, Solid, n.o.s. (D007)

DOT Hazard Class: 9 ; Packing Group: III

DOT Identification Number: NA 3077

DOT Emergency Response Guide 31 Applies

Section 2

HAZARDOUS INGREDIENTS

Ingredient:	CAS Number:	Content %:	ACGIH-TLV	Toxicology:
Aluminum	7429-90-5	0-5	10 mg/m ³	No Data Available
Chromium	7440-47-3	0-15	0.5 mg/m ³	2.75 mg/kg (Rat, Oral)
Copper	7440-50-8	0-10	1.0 mg/m ³	0.35 mg/kg (Mouse, Oral)
Nickel	7440-02-0	0-10	1.0 mg/m ³	No Data Available
Zinc	7440-66-6	0-5	none established	No Data Available

Section 3

PHYSICAL AND REACTIVITY DATA

Description: Moist, Sandy consistency

Brown to Black colored

Water Content 10-20% by weight

Specific Gravity: 2.0 to 3.0

Solubility: Insoluble in water

Density: 100 to 150 lbs/cu/ft

Incompatible Reactivity: Extreme heat sources, Oxidants

Vapor Pressure: Insignificant

Stability: Avoid contact with acids, extreme heat

Polymerization: Will not occur

Boiling Point: Above 2000°C

Melting Point: Above 1000°C

pH: 7.0 to 10.0

Odor: Nil

Section 4

FIRE AND EXPLOSION DATA

Flashpoint: Nonflammable, under normal conditions

Oxidation: Non-oxidizing

Special Firefighting Procedures: Dry Chemical

Explosive: Non-explosive

Product Decomposition... (Due to Fire or Explosion): Hydrogen gas, ZnO (under extreme external heat)

NFPA

Fire Diamond



Section 5

TOXICITY

Listed Carcinogen component: Chromium, Nickel Toxicology: See Sec. 2 (Chromium, Nickel) Route of Entry: Inhalation and Ingestion

Section 6

HEALTH EFFECTS AND FIRST AID

Inhalation: Dust may irritate mucous membranes and upper respiratory tract. Remove to fresh air and treat symptoms.

Ingestion: Rare in industry. Induce vomiting (do not induce vomiting or give a liquid to an unconscious person) and call a physician.

Eyes: Dust may irritate eyes. Wash with copious amounts of water for 15 minutes, if effects persist, call a physician.

Skin: Dust may irritate skin, causing forms of eczema. Wash with soap and water.

Long-Term Effects: Chronic overexposure may affect the following target organs or body systems—blood, digestive, respiratory, lungs, liver, kidneys and skin.

Comments: Special attention should be given to employees with anemia, restricted respiratory abilities, lung cancer, permanent kidney damage and metal-sensitive skin or skin lesions.

Section 7

PRECAUTIONS FOR SAFE HANDLING

Handling: Good personal and industrial hygiene should always be practiced. It is recommended that personal protective equipment be used by personnel who will come in contact with the material. The equipment should include eye protection, respirator and gloves.

Storage: Keep covered and avoid conditions where wind could cause dispersal. Do not eat, drink or smoke where material is handled to avoid inhalation or ingestion. Store in a dry area under cover from rain.

Spills: Cleaning procedures should not create excessive dust. Vacuum when possible. Package material and send to World Resources Company at above address.

Section 8

CONTROL MEASURES

Respiratory Protection: NIOSH-MSHA approved respirators as required.

Eye Protection: Safety Glasses recommended.

Other Protective Equipment: Coveralls are recommended, but not required.

Hand Protection: Gloves recommended.

Section 9

GENERATORS VERIFICATION

This MSDS is provided solely for informational purposes and no warranty or responsibility is extended even though reasonable precautions have been taken in the preparation of the data contained for this recyclable material. To the best of my knowledge this MSDS describes the recyclable material listed on the attached Manifest Number: 77007 Telephone: (206) 823-5800 Date: 10-23-97

Company Name and Address: Alaskan Copper Works 628 Hanford st. Seattle Wa 98134

Signature: _____

AZF-WRC 3/94

AKC-0017822

MATERIAL IDENTIFICATION

DOT BASIC SHIPPING DESCRIPTION AND TECHNICAL NAME:
Hazardous waste, solid, n.o.s. (D007)

1996
NORTH AMERICAN
EMERGENCY RESPONSE
GUIDEBOOK

TAKEN FROM GUIDE 171 OF THE 1996 NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK

(Underlined text applies directly to the material listed above)

POTENTIAL HAZARDS

FIRE OR EXPLOSION

- Some may burn, but none ignite readily.
- Some may polymerize (P) explosively when heated or involved in a fire.
- Containers may explode when heated.
- Some may be transported hot.

HEALTH

- Inhalation of material may be harmful.
- Contact may cause burns to skin and eyes.
- Inhalation of Asbestos dust may have a damaging effect on the lungs.
- Fire may produce irritating, corrosive and/or toxic gases.
- Runoff from fire control may cause pollution.

PUBLIC SAFETY

- CALL CHEMTREC at 1-800-424-9300 FOR EMERGENCY ASSISTANCE (Use CHEMTREC Company Code "W00R").
- Isolate spill or leak area immediately for at least 10 to 25 meters (30-80 feet) in all directions.
- Keep unauthorized personnel away.
- Stay upwind.

PROTECTIVE CLOTHING

- Wear positive pressure self-contained breathing apparatus (SCBA).
- Structural firefighters' protective clothing will only provide limited protection.

EVACUATION

Fire

- If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

EMERGENCY RESPONSE

FIRE

Small Fires

- Dry chemical, CO₂, water spray or regular foam.

Large Fires:

- Water spray, fog or regular foam.
- Move containers from fire area if you can do it without risk.
- Do not scatter spilled material with high pressure water streams.
- Dike fire-control water for later disposal.

Fire Involving Tanks:

- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from the ends of tanks.

SPILL OR LEAK

- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Prevent dust cloud.
- Avoid inhalation of asbestos dust.

Small Dry Spills

- With clean shovel, place material into clean, dry container and cover loosely; move containers from spill area.

Small Spills

- Take up with sand or other noncombustible absorbent material and place into containers for later disposal.

Large Spills

- Dike far ahead of liquid spill for later disposal.
- Cover powder spill with plastic sheet or tarp to minimize spreading.
- Prevent entry into waterways, sewers, basements or confined areas.

FIRST AID

- Move victim to fresh air.
- Call emergency medical care.
- Apply artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

AZF WRC 8/18/96